

NVENIA
A DURAVANT COMPANY

**ARPAC BRAND
BRANDPAC BPMP SERIES**

BRANDPAC™ BPMP-5000 SERIES

The BRANDPAC™ BPMP-5000 SERIES is the champion in multipacking equipment for medium to high volume food and beverage industries. This versatile continuous motion bottom overlap shrink wrapping system operates on demand, without a seal bar to shrink wrap up to 75 unsupported multipacks or trays per minute, depending on the height and weight of the product.

Using single roll print registered polyethylene film, the BPMP-5000 system ensures accurate placement of printed logos, graphics and advertising messages on each bundle with a bull's eye enclosure.

Print registered film provides an attractive forum for your retail marketing message at a fraction of the cost of traditional paperboard packaging. The finished package is an easy to carry multipack that is attractive to the consumer.

Servo technology ensures the wrapper provides gentle product handling and precise wrapping. This automatic system accumulates product into patterns, wraps print registered film around the patterned product and shrinks the film to make multipacks. The user friendly NVenia operator interface manages the complete system with simple entry and self diagnostics ensuring reliable performance.


Quick product changeovers take place in less than 15 minutes with the BPMP's pre-programmed product settings, drop-in color coded spacers for infeed lane guides and side film splicer. New product parameters are selected from one of 16 pre-programmed settings.

The BPMP-5000 is a fully integrated shrink film multipacker easily integrated with other packaging equipment.

Model Shown With Optional Swivel Mounted Control Panel And Standard Tunnel




THE PROCESS FOR BOTTOM OVERLAP WRAPPING




Servo Controlled Film Feed for Exact Print Registration



Film Cut from the Supply Roll



Smooth Motion Wrapping



Bottom Overlap Wrapped Sleeve to Shrink Tunnel

Single Roll Clear/Print Registered Film Multipacker

GROUPERS

nVenia designs different groupers to accommodate a variety of product shapes. This assembly is used to separate products into pack groups and control the flow of product into the pacing flight bar assembly. In the case of tray-loaded products, the collator serves to pace and release products into the BPMP-5000



Adjustable Starwheel

- 15 minute changeover (servo)
- 45 minute changeover (mechanical)
- Accommodates round products only



Shuttle Grouper

- 30 minute tool-less changeover
- Accommodates round, non-round and square products
- Lane divider is required for non round and square products



Servo Adjusted Side Belt

- 10 minute rapid changeover
- Accommodates round products only
- Tool-less servo adjustment of grouper



Mechanically Adjusted Side Belt

- 2 hour changeover to replace gripper belts and drive gears
- Accommodates round products only
- Fixed size gripper belt



Custom Groupers Available Upon Request


Our primary focus is finding engineered solutions to your packaging needs. Many of our groupers are custom designed to our customer's exact specifications.

MACHINE FEATURES

- Printed film registration for accurate placement of printed graphics
- Heavy-duty frame construction with welded joints for high durability
- Laser cut and CNC machined components for maximum precision
- Powder coat finish that provides a durable scratch resistant surface and prevents corrosion
- Fully guarded for safety and easy access
- Gentle product handling with servo or mechanical driven collating system
- Servo or mechanical driven overwrap for smooth and efficient film wrapping
- Servo-driven mechanical film feed is low maintenance and can adapt to a wide range of film lengths (no vacuum)
- Side mounted film rack and film splicing bar for quick and easy film changeover with little or no downtime
- Allen Bradley® programmable controller
- nVenia operator interface features a color touchscreen with me sage display and self-diagnostics
- Low film alert warns that a changeover may soon be necessary
- Easy machine adjustments for reliable and quick product changeover
- Right or left hand operator station and film rack
- Air conditioning standard on main electrical enclosure
- Optional tray conversion for tool-less changeover from mult pack to tray shrink wrapped products
- Optional machine mounted jib crane to facilitate film loading
- Optional product turning conveyor
- Optional wet product seal conveyor extends machine length by 48"
- Optional side product transfer to infeed extends machine length by 48"

Groupers							
Machine Models	Speed	Servo Star Wheel	Mech. Star Wheel	Shuttle	Servo Side Belts	Power	Machine Length
5100	Up to 35	NA	NA	•	NA	75A (65kW)	311"
5200	Up to 45	•	•	•	NA	75A (65kW)	287"
5300	Up to 60	•	•	NA	•	97A (72kW)	310"
5400	Up to 75	•	•	NA	•	125A (99kW)	410"

*Note: length of machine relates to model



Model Shown: BPMP-5341, right hand side, opposite hand available on request

SPECIFICATIONS

Speed

- Output speed: up to 75 packages per minute (see chart)
- Power Requirements

Electrical

- 480VAC, 3Ph, 60Hz, (see chart) Other voltages available on request

Pneumatic

- 80 psi, 30 CFM at 50 cycles per minute
- Approx. Shipping Weight
- 4,950 lbs. w/conveyors

Product Range

- 6" to 18" width across machine (AM)
- 3" to 12" length down machine (DM)
- 3" to 12" height

Film

- Film width: 26" max., 6" min.
- Clear, print registered or randomly printed
- Film roll diameter up to 20" with a 3" core
- Film gauge: 1.75 mil to 2.5 mil polyethylene

HEADQUARTERS

750 N. Wood Dale Road
Wood Dale, IL 60191

CONTACT US

info@nVenia.com
800.253.5103
www.nVenia.com

